

Super

Labeller with a speed of 80 mt/minute



Super is the labeller to meet the highest and most specific requirements of the packaging lines, thanks to a powerful stepper motor, attaining a speed of 80 mt/minute and to a paper reel holder supporting label reels up to 400 mm of diameter, ensuring a large production autonomy and offering the possibility of an automatic changeover between two labellers on line, with no down time.

The high speed is ensured together with the highest degree of precision, thanks to the working of a motorized rewinder, keeping the backing paper taut, while a sensor driven by the oscillating roll adjusts and determines the maximum load of the rewound paper. The HS version attains a speed of 120 mt/minute.

Technical specifications

Dispensing speed

max 80 mt/min / Super 1.3
max 60 mt/min / Super 2.5
max 120 mt/min / Super 1.3 HS

Motorization

stepper motor

Compressed air

6 bar with printing unit

Dispensing width

min 8 mm, max 128 mm / Super 1.3
min 8 mm, max 248 mm / Super 2.5

Outside reel diameter

380 mm

Inside reel diameter

40-75 mm

Machine size

length 1186, width 581, height 716 mm / Super 1.3
length 1186, width 684, height 745 mm / Super 2.5

Power supply

115/230/240 Volt, 50-60 Hz

Electrical input

350 W

Electrical protection

Ip55

Noise level

70dB